TEMPORARY TRAFFIC CONTROL TYPICAL APPLICATION

IMPORTANT:
THIS DRAWING SHALL BE USED IN
COMBINATION WITH THE GENERAL
NOTES MD 104.00-01 - MD 104.00-18 AND
STANDARD DETAILS MD 104.01-01 MD 104.01-62

NOTES:

IF THE LEAD WORK VEHICLE IS TRAVELING AT THE POSTED SPEED LIMIT OR WITHIN 15 MPH OF IT, THEN NO BACK UP VEHICLE IS NECESSARY.

IN URBAN AREAS THE DISTANCE MAINTAINED BETWEEN VEHICLES MAY BE DECREASED AS NEEDED.

VEHICLES SHALL DISPLAY FLASHING HAZARD/PARKING LIGHTS IN FRONT AND REAR.

VEHICLES THAT STOP INTERMITTENTLY SHOULD BE DRIVEN, OR PARKED, OFF THE TRAVELED LANE WHENEVER POSSIBLE.

TMA MAY BE USED ON WORK VEHICLE, IF PROTECTION VEHICLE IS NOT AVAILABLE.


KEY:



APPROVED VEHICLE SAFETY LIGHT

DIRECTION OF TRAFFIC

TRUCK MOUNTED ATTENUATOR (TMA)



SPECIFICATION 104

APPROVED

DIRECTOR - OFFICE OF TRAFFIC AND SAFETY

APPROVAL • SHA
REVISIONS HIGHWAY ADMINISTRATION
APPROVAL 8-20-03 APPROVAL 9-23-03
REVISED REVISED
REVISED REVISED
REVISED REVISED
REVISED REVISED
REVISED REVISED
REVISED REVISED

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION

STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES

MOBILE OPERATION/2-LANE, 2-WAY ALL SPEEDS/0-15 MIN., AND MOVING SLOW

STANDARD NO.

MD 104.02-15